

# VIRGO LIFEBOUOY

## Item 12010



The Virgo Lifebuoy is certified in accordance with SOLAS 74/83, EC 96/98, M.E.D. Regulations and Ministerial Decree no. 385, being designed to ensure maximum safety at sea.

### Compliant with recreational boating regulations.

Made of high-density polyethylene with closed-cell polyurethane core, the materials provide extensive strength, lasting durability and excellent buoyancy, even in harsh marine conditions. Able to withstand temperatures from +65 °C to -30 °C, falling into the sea from heights of over 30 metres, repeated impacts on hard surfaces such as concrete, prolonged immersion in diesel fuel for 24 hours, exposure to open flame and high-load tension tests for extended periods. The lifebuoy is equipped with a 3-metre rope with a 10-mm diameter to facilitate recovery.

The use of a self-righting floating buoy is recommended for signalling and recovery.  
Item: 14010/LED

### Suitable for both recreational and professional vessels.



### SPARE PARTS

FEATURES		SPARE PARTS	
Code: 12010		 <b>Self-righting buoy light 14010/LED</b>	
<b>Type</b>	Lifebuoy	Self-righting buoy light for SOLAS M.E.D. lifebuoy. Without internal batteries.	
<b>Weight</b>	> 2.5 kg	 <b>Floating rope 14000</b>	
<b>Size</b>	Dimensions: Outer Ø 62.5 cm - Inner Ø 40.5 cm	Floating rope, orange in colour, 30 meters long.	
<b>Colour</b>	Orange-Red		
<b>Reflective band</b>	4 reflective bands		