

# ALTURA LIFEBOUY

Item 12000 – 12005



The Altura Lifebuoy is certified in accordance with SOLAS M.E.D., IMO Resolutions, MSC 81(70), MSC 226(82) regulations and Ministerial Decree no. 385, being designed to ensure maximum safety at sea.

Made of high-density, high-strength material to ensure reliable performance and lasting durability, even in the most extreme conditions. Able to withstand temperatures from +65 °C to -30 °C, falling into the sea from heights of over 30 metres, repeated impacts on hard surfaces such as concrete, prolonged immersion in diesel fuel for 24 hours, exposure to open flames and high-load tension tests for extended periods.

The lifebuoy is equipped with a 3.35-metre rope with a 10-mm diameter to facilitate recovery.

The use of a self-righting floating buoy is recommended for signalling and recovery.



Item: 14010/LED

**Suitable for commercial vessels, recreational boats and offshore installations.**



## SPARE PARTS

FEATURES	
Code: 12000 - 12005	
<b>Type</b>	Lifebuoy
<b>Weight</b>	OIC 11(12000): > 2.5 kg - 12005: 4 kg
<b>Dimensions</b>	Dimensions: Outer Ø: 73 cm - Inner Ø: 43 cm
<b>Colour</b>	Orange-Red
<b>Reflective band</b>	4 reflective bands

	<b>Self-righting buoy light 14010/LED</b>
	Self-righting buoy light for SOLAS M.E.D. lifebuoy. Without internal batteries.
	<b>Floating rope 14000</b>
	Floating rope, orange in colour, 30 metres in length.