

INFLATABLE HORSESHOE LIFEBUOY

Art. 12041

The 150 N Inflatable Horseshoe Lifebuoy is a lifesaving device designed for the rapid recovery of a person overboard. Compact and lightweight when stowed, it is intended for immediate deployment in emergency situations on both recreational and professional vessels.

The inflation system features both **automatic activation** (upon contact with water) and **manual activation**, ensuring maximum versatility in use. Rapid inflation is provided by a 33 g CO₂ cylinder, allowing the device to reach full buoyancy within seconds.

MEANS FEATURES:

- Automatic inflation
- 150 N buoyancy
- High-visibility reflective tape
- Oral inflation tube
- Emergency whistle
- Compact and lightweight



Inflation
Mechanism

Whistle and
Oral Inflation
Tube




Soft, Compact and Durable Protective Cover


INSTRUCTIONS FOR USE




Remove the device
from the
carrying handle.



Throw it toward
the person
in difficulty.



The rescuer automatically
inflates upon contact
with the water.



The person can grasp
the rescuer
and be recovered.

The horseshoe-shaped design provides effective buoyancy support, helping to keep the wearer in a stable position while facilitating recovery operations. The device is also equipped with high-visibility reflective tape, improving detection in low-light and reduced-visibility conditions.

For enhanced safety, it features an integrated emergency whistle, allowing the user to attract attention during rescue situations.

Thanks to its practical design, reliability, and rapid deployment, it is an essential safety device for onboard emergency preparedness and prompt man-overboard response.



Features	
Product Type	Inflatable Horseshoe Lifebuoy
Category	Buoyancy Aid
Buoyancy	150 N
Inflation System	Automatic
Activation	Water-Activated Bobbin and Manual Pull Cord
CO ₂ Cylinder	33 g, Replaceable
Oral tube	Integrated Emergency Relief Valve
Color	High Visibility (Fluorescent Yellow)
Features	Reflective Tape and Emergency Whistle
Weight	~550 g
Operating Environment	Sea, Lakes and Inland Waters
Application	Man Overboard (MOB) Emergency
Maintenance	Recommended Inspection Every 2 Years

OPTIONAL ACCESSORIES

	LED Light cod. 03030
	Activates automatically upon contact with water, providing enhanced visibility up to 1 nautical mile . Certified to SOLAS, MED (Marine Equipment Directive), and USCG Approved standards.

	Floating rope cod.14000
	30 m orange floating lifeline