SKIPPER EVO 275

Inflatable life jacket certified to ISO 12402-2, Class 275. **Actual buoyancy: 290**. Integrated ISO 12401 safety harness with acetal resin quick-release buckle and side adjustment.
Designed for recreational activities carried out offshore and/or in adverse weather conditions, allowing the wearer to safely await rescue even in rough waters. **Ensures maximum safety for all types of navigation.** Easy and intuitive to wear, it provides maximum freedom of movement and mobility during navigation manoeuvres on board.

MAIN CHARACTERISTICS:

- Ergonomic collar in breathable mesh fabric for optimal comfort
- Rear support strap
- High-strength zippered cover
- Frontal quick-release buckle
- Side adjustment with stainless-steel buckle
- Double safety line attachment ring
- Rear rescue handle positioned at the nape
- Integrated frontal lifting handle compliant with regulatory requirements
- Adjustable crotch strap

Available in two colour variants:

BLACK





09675/24/HX/EVO/NE

BLUE





09675/24/HX/EVO/BL



FABRIC BACKPACK

Crotch strap



CODE	PRODUCT NAME	ACTIVATION	ACTIVATOR
09675/24/HX/EVO/BL	SKIPPER LIGHT 275 BLUE	AUTOMATIC	UMK MK5
09676/24/HX/EVO/BL	SKIPPER LIGHT 275 BLUE	MANUAL	UML MIRCOMANUAL
09675/24/HX/H/EVO/BL	SKIPPER LIGHT 275 BLUE	AUTOMATIC	HAMMAR MA1/EC
09675/24/HX/EVO/NE	SKIPPER LIGHT 275 BLACK	AUTOMATIC	UML MK5
09676/24/HX/EVO/NE	SKIPPER LIGHT 275 BLACK	MANUAL	UML MICROMANUAL
09675/24/HX/H/EVO/NE	SKIPPER LIGHT 275 BLACK	AUTOMATIC	HAMMAR MA1/EC

VELERIA SAN GIORGIO®
LIFEJACKET MANUFACTURER

Date: 25/05/2026
Rev.: 01

FEATURES Code: 09675/24/HX/EVO/BL – 09675/24/HX/EVO/H/BL – 09675/24/HX/EVO/BL – 09675/24/HX/EVO/NE – 09675/24/HX/EVO/H/NE – 09676/24/HX/EVO/NE	
Type	Inflatable life vest
Available triggers	UML MK5- Automatic:09675/24/HX/EVO/BL - 09675/24/HX/EVO/NE UML MICROMANUAL- Manual: 09676/24/HX/EVO/BL - 09676/24/HX/EVO/NE HAMMAR MA1/EC-Automatic:09675/24/HX/EVO/H/BL - 09675/24/HX/EVO/H/NE
Canister	60 g Thread ½" GAS
Real buoyancy	290 N
Class	275 N
Closure system	Safety harness with 45-mm webbing, closure system with quick-release buckle in acetal resin and side adjustment with stainless-steel sliding buckle plus double safety lanyard attachment.
Certifications	ISO 12402-2, ISO 12401
Size	Adult
Supported weight	>40 kg
Waist circumference	80–125 cm
Cover	PL 600D PU COATED
Chamber	Material: PA 420 PU coated, yellow.
Packaging	Carry bag with PL 600D PU coated mesh.
Product dimensions	50x30x5 cm +/- 5%
Product weight	09675/24/HX/EVO/BL - 09675/24/HX/EVO/NE (1700 gr circa) 09676/24/HX/EVO/BL - 09676/24/HX/EVO/NE (1650 gr circa) 09675/24/HX/EVO/H/BL - 09675/24/HX/EVO/H/NE (1700 gr circa)
Packaging	60x40x40 cm (13 per box)
Warranty	24 months
Inspection	Every 24 months
Accessories	Safety line, splash guard cap, automatic emergency light.
Spare parts	Whistle, rearming kit, crotch strap.
Veleria San Giorgio reserves the right to modify the technical specifications without prior notice.	

DONNING INSTRUCTIONS



1. Put on the life jacket



2. Fasten the buckle



3. Adjust the waist strap

Date: 25/05/2026
Rev.: 01

Single-compartment buoyancy chamber in PA 420 PU coated fabric with electronically-controlled high-frequency welded seams. This ensures an optimal positioning in the water and perfect stability. The buoyancy is enough to rotate and tilt an unconscious person face-up, keeping the airway above water. Even with the chamber inflated, it is possible to easily swim to safety or quickly climb onto a liferaft.

ACTIVATION SYSTEMS:

• Automatic - Upon falling into the water, the system is submerged and automatically inflates the buoyancy chamber within 5 seconds. Automatic activation is possible with the UML MK5 salt-water trigger, using the dissolution of a water-soluble tablet, or with the Hammar MA1 hydrostatic trigger, activated by water pressure when submerged to at least 10 cm.

• Manual - The system is activated by pulling the dedicated handle. It is supplied with the UML MICROMANUAL manual trigger and is activated exclusively by hand.

• Oral - This inflation method occurs via the mouth tube, non-return valve and protective cap. To inflate the chamber, simply blow into the mouth tube.



SPARE PARTS



Whistle code 25180

A mandatory accessory that emits an emergency acoustic signal. Certified to ISO 12402-8.

Rearming kit:
UML MK5: rearming kit (26238), 38 g cylinder
UML MICROMANUAL: rearming kit (26238), 38 g cylinder
HAMMAR MA1/EC: rearming kit (26238), 38 g cylinder

ACCESSORIES



Crotch strap code 09146

The use of this accessory improves the tilt, stability and positioning of the body in water.



Crotch strap code 09148

The use of this accessory improves the tilt, stability and positioning of the body in water.



Elastic with 2 aluminium hooks - code 11177/OVER

Safety lanyard
Length: 2 metres
Material: aluminium



2 aluminium hooks code 11174/OVER

Safety lanyard
Length: 2 metres
Material: aluminium



3 aluminium hooks code 11175/OVER

Safety lanyard
Length: 1.4–2 metres
Material: aluminium



Elastic with 2 steel hooks - code 11176/OVER

Safety lanyard
Length: 2 metres
Material: stainless steel



2 steel hooks cod 11173/OVER

Safety lanyard
Length: 2 metres
Material: stainless steel



Steel hook + ring code 11178/OVER

Safety lanyard
Length: 2 metres
Material: stainless steel



Splash guard cap code 09145/SK

Reduces the risk of secondary drowning caused by inhaling water spray. Improves visibility of the survivor.



LED light code 03030

Activates automatically upon falling into the water. Provides visibility up to one mile. Certified SOLAS M.E.D. and USCG approved.

Remember to conduct a periodic inspection. Book an inspection now by emailing us at info@veleriasangiorgio.com or through the website.

For more information, please call +39 0185 467701 or visit our website veleriasangiorgio.com.

To buy or learn more about this product, please refer to the QR Code or visit veleriasangiorgio.com.

LIFE JACKETS AND LIFEBELTS, FLAGS AND BANNERS, TECHNICAL ITEMS, PERSONAL PROTECTIVE EQUIPMENT AND SAFETY GEAR FOR CIVILIAN AND MILITARY FIELDS Via Alcide De Gasperi, 37H - 16030 Casarza Ligure - Genoa - Italy Tel. +39 0185 467701 - Fax +39 0185 467050 - info@veleriasangiorgio.com - www.veleriasangiorgio.com

VELERIA SAN GIORGIO®
LIFEJACKET MANUFACTURER

Date: 25/05/2026
Rev.: 01

ESCLUSIVE SAFETY TECNOLOGIES

Safety at sea is our main priority. We manage all research, design and production processes with the utmost care so as to offer certified equipment for all nautical fields, with the highest production standards. All research and development activities are certified by the Department of Applied Science and Technology of the Polytechnic University of Turin, in accordance with EU regulations.

THE PRODUCTION PROCESS AND TRACEABILITY

With the aim of making inflatable life jackets more reliable, in 1994 Veleria San Giorgio introduced the Unique Product Code system. As the only manufacturer in the world to employ this type of technology, VSG is now able to identify all materials and individual components utilised through distinct alphanumeric codes.




CERTIFICATO N. 26/91/S
CERTIFICATE No.
SI CERTIFICA CHE IL SISTEMA DI GESTIONE PER LA QUALITÀ DI
IT IS HEREBY CERTIFIED THAT THE QUALITY MANAGEMENT SYSTEM OF
VELERIA SAN GIORGIO S.R.L.
VIA A DE GASPERI 37H 16030 Casarza Ligure (GE) ITALIA
NELLE SEGUENTI UNITÀ OPERATIVE / IN THE FOLLOWING OPERATIONAL UNITS
VIA A DE GASPERI 37H 16030 Casarza Ligure (GE) ITALIA
È CONFORME ALLA NORMA / IS IN COMPLIANCE WITH THE STANDARD
ISO 9001:2015

Production processes are controlled via software specially developed by VSG, covering 100% of production so each product can be traced back to its buyer with absolute precision. This drastically reduces manufacturing defects (less than 1/10000 of returns), guaranteeing each buyer a unique product in the truest sense of the word and – most importantly – the highest degree of safety when needed.

Thanks to their ergonomic features, our life jackets guarantee an optimal position in the water and great stability. In addition, the vests offer enough buoyancy to rotate and tilt an unconscious person, so as to always keep the airway out of the water.

